DC-DC Converters

DLS-4824DC Series

48 to 24V DC Power Supply



- I High efficiency
- I High precision
- I Heavy duty applications

DLS-4824DC Series DC-DC Converter Datasheet 38-62 VDC Input and 24 VDC output



Applications:

- Automotive
- Telecommunications
- Distributed power
- Defense
- Aerospace
- Medical
- And other applications requiring high efficiency

General Description:

Nelso[™] is manufacturer of high precision, high reliability DC-DC Converter in Kolkata, India. This product is designed to provide 48V to 24V power conversion for heavy duty applications.

Features:

- Input-output isolation
- High efficiency
- High precision
- Wide input voltage range
- Over-voltage protection
- Under voltage protection
- Reverse polarity protection
- Voltage transient protection
- Over load protection
- Short circuit protection

Quick Reference Data:

Мс	odel No.		Output Voltage	Output Current	Efficiency	Ripple
DLS-	4824DC	48V DC	24V DC	1A 3A 5A 8A 10A	85%	<150mV

Electrical Specification:

Input Voltage:	38V DC to 62V DC			
Output Voltage:	24V DC (Regulated)			
Output Current:	1, 3, 5, 8, 10 A			
Reverse Polarity:	85V DC			
Line Regulation:	±1%			
Load Regulation:	± 5% at terminal block			
Switching Frequency:	80 KHz			
Efficiency:	80% Typical			
Topology:	Transformer isolated forward converter			
Operating Temperature:	-40 to 80 °C			
Humidity:	Up to 95% RH			
Heat Sink Temperature:	100°C			
Storage Temperature Range:	- 55°C to + 105°C			
Weight:	475gm			
Dimension (Height x width x depth):	150 x 150 x 63 mm			