DC-DC Converters

DLS-2448DC Series

24 to 48V DC Power Supply



- I High efficiency
- I High precision
- I Heavy duty applications

DLS-2448DC Series DC-DC Converter Datasheet 22-28 VDC Input and 48VDC output



Applications:

- Automotive
- Telecommunications
- Distributed power
- Defense
- Aerospace
- Medical
- And other applications requiring high efficiency

General Description:

Nelso[™] is manufacturer of high precision, high reliability DC-DC Converter in Kolkata, India. This product is designed to provide 24V to 48V power conversion for heavy duty applications.

Features:

- Input-output isolation
- High efficiency
- High precision
- Wide input voltage range
- Over-voltage protection
- Under voltage protection
- Reverse polarity protection
- Voltage transient protection
- Over load protection
- Short circuit protection

Quick Reference Data:

| Model No. | Input Voltage | Output Voltage | Output Current | Efficiency | Ripple |
|------------|------------------|-------------------|----------------------|------------|--------|
| DLS-2448DC | 24V DC | 48V DC | 1A 3A 5A 8A | 85% | <150mV |

Electrical Specification:

| Input Voltage: | 22V DC to 28V DC | | |
|-------------------------------------|----------------------------------------|--|--|
| Output Voltage: | 48V DC (Regulated) | | |
| Output Current: | 1, 3, 5, 8 A | | |
| Reverse Polarity: | 30V DC | | |
| Line Regulation: | ±1% | | |
| Load Regulation: | ± 5% at terminal block | | |
| Switching Frequency: | 80 KHz | | |
| Efficiency: | 80% Typical | | |
| Topology: | Transformer isolated forward converter | | |
| Operating Temperature: | -40 to 80 °C | | |
| Humidity: | Up to 95% RH | | |
| Heat Sink Temperature: | 100°C | | |
| Storage Temperature Range: | - 55°C to + 105°C | | |
| Weight: | 1200gm | | |
| Dimension (Height x width x depth): | 195 x 150 x 75 mm | | |